



ALPHA MTX-1000 is a robust LED lighting unit designed for reliable performance in harsh environmental and climatic conditions. All components use corrosion-, wear- and impact-resistant materials for a long service life.

Its flexible mounting system supports secure indoor and outdoor installation on walls, ceilings, towers, poles and hard-to-reach locations.

High optical performance delivers the required illumination, while electronic protection supports system safety against voltage surges. The mechanical design withstands impact and demanding operating conditions.


Galvanised metal parts and corrosion- and wear-resistant coatings on fasteners help preserve structural integrity and surface protection over long-term use.



Powered by Nichia LEDs



AC-DIRECT
ALTERNATING CURRENT DIRECT DRIVER



IP68

NICHIA
LED

10°-90°
120°

AC

LONG
LIFE

DIMMABLE

IK
09T

no
UV

CE

no
IR

ALU.

cos φ 0.98
100% PF

CRI
80+

RoHS


Energy
Saver

no
IR

no
UV





5 Years
WARRANTY
Parts & Labour
MAX
LIGHTING

General Information



Model / variant	MTX-1000-120A	MTX-1000-120AL	MTX-1000-120D	MTX-1000-120DL
Product number	27M001974	27M001975	27M001976	27M001977
Product type	LED high-bay luminaire			
Dimensions - H × W × L	240 × 175 × 400 mm			
Housing / material	Aluminium (AL6063) / Galvanised			
Weight	4.00 kg	4.00 kg	4.50 kg	4.50 kg
Colour / RAL	Matt black / 9017 • Matt red / 3020			
Minimum order	1 unit			

Technical Specifications



Power (@ 240 VAC)	120 W (±5%)			
Input voltage	240 VAC			
Luminous flux	18,000 lm			
Luminous efficacy	150 lm/W			
Beam angle	120°	10°-90°	120°	10°-90°
Colour temperature	2000 ~ 6500 K			
Colour rendering index (CRI)	>80			
Power factor (cos φ)	0.98			
IP rating	IP68			
Operating temperature	-35 °C ~ +65 °C			
Product lifetime	25 Years			
Warranty	5 Years			
LED type / quantity	Nichia SMD 3030 / 96 pcs			
Power supply system	AC Direct™ (A / AL) • External driver (D / DL)			
Power supply brand	MAX	MAX	OEM	OEM
Electrical connection	L / N / PE			
Connection cable	3 × 0.75 mm² × 500 mm H05RN-F			
Compliance / standard	CE, RoHS, TS EN 60598-2-5			
Management systems	ISO 9001 / ISO 14001 / ISO 45001			

Installation, commissioning, maintenance and dismantling require qualified personnel and compliance with applicable electrical and workplace safety rules. The MAX Lighting brand and product patent/design rights belong to STAR ENDUSTRI A.Ş. Made in Türkiye with 100% Turkish capital.